



SAFETY DATA SHEET

1. Identification

Product number 1000009084
Product identifier **TERAND PENETRANT LUBRICANT DEMOISTURANT PROTECTANT**
Revision date 03-31-2016
Company information CPC
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 800-327-1835
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 12
Supersedes date 02-11-2016
Recommended use LUBRICANT
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas
Health hazards Reproductive toxicity (fertility) Category 2
Aspiration hazard Category 1
OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of damaging fertility.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention.

Storage

Store locked up. Protect from sunlight. Store in a well-ventilated place.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Combustible.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
White Mineral Oil (petroleum)		8042-47-5	80 - 90
Dipropylene Glycol Monomethyl Ether		34590-94-8	2.5 - 10
Methyl Silicone		556-67-2	2.5 - 10
Carbon Dioxide		124-38-9	1 - 2.5

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light Naphthenic		64742-53-6	0.1 - 1
Distillates, (Petroleum), Hydrotreated Heavy Paraffinic		64742-54-7	0.1 - 1
Other components below reportable levels			2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No specific first aid measures noted.
Ingestion	Not likely, due to the form of the product.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	PEL	5000 ppm 600 mg/m3
		100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	TWA	5000 ppm
	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3
		30000 ppm
	TWA	9000 mg/m3
		5000 ppm
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	STEL	900 mg/m3
		150 ppm
	TWA	600 mg/m3
		100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
------------	------	-------

Methyl Silicone (CAS 556-67-2)	TWA	10 ppm
--------------------------------	-----	--------

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines**US - California OELs: Skin designation**

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Gas.

Form Aerosol. Compressed gas.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point 311.6 °F (155.3 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

Other information

Aerosol spray enclosed space

Deflagration density	1534.65 g/cm3
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.845 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, sparks and open flame. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)		
Acute		
Dermal		
LD50	Rabbit	9510 mg/kg, 24 Hours 10 ml/kg, 24 Hours
	Rat	> 19020 mg/kg, Hours > 20 ml/kg, Hours
Inhalation		
LC50	Rat	> 553 ppm, 8 Hours > 275 ppm, 7 Hours

Components	Species	Test Results
Oral		
LD50	Dog	7.5 ml/kg
	Rat	> 5000 mg/kg
		5.4 ml/kg
Distillates (Petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	2.18 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Distillates, (Petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	2.18 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Methyl Silicone (CAS 556-67-2)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
		> 2.5 ml/kg
Inhalation		
<i>Aerosol</i>		
LC50	Rat	36 mg/l, 4 Hours
Oral		
LD50	Mouse	1700 mg/kg
	Rat	> 4800 mg/kg
White Mineral Oil (petroleum) (CAS 8042-47-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	2.18 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Distillates (Petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)		
Aquatic		
Crustacea	EC50 Daphnia	1000.0001 mg/L, 48 Hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, non-flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.2

Subsidiary risk -

Label(s) 2.2

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 306

Packaging non bulk None

Packaging bulk	None
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
DOT	



IATA; IMDG



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (Petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)
Distillates, (Petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)
Methyl Silicone (CAS 556-67-2)

US. Massachusetts RTK - Substance List

Carbon Dioxide (CAS 124-38-9)
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)
Distillates (Petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9)
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (CAS 124-38-9)
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-03-2015

Revision date 03-31-2016

Version # 12

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names