



# SAFETY DATA SHEET

## 1. Identification

**Product number** 1000009118  
**Product identifier** 16 OZ TERAND IND FOAM DEGREAS 2 LB 12PK  
**Revision date** 10-25-2018  
**Company information** CPC  
1000 INTEGRAM DRIVE  
PACIFIC, MO 63069 United States  
**Company phone** General Assistance 800-327-1835  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 03  
**Supersedes date** 02-14-2017  
**Recommended use** CLEANER  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Skin corrosion/irritation Category 2  
Serious eye damage/eye irritation Category 2B  
Sensitization, skin Category 1  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger  
**Hazard statement** Extremely flammable aerosol. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation.

### Precautionary statement

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.

#### Response

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

#### Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Supplemental information** None.

## 3. Composition/information on ingredients

### Mixtures

| Chemical name | Common name and synonyms | CAS number | %        |
|---------------|--------------------------|------------|----------|
| Butane        |                          | 106-97-8   | 2.5 - 10 |

Product name: 16 OZ TERAND IND FOAM DEGREAS 2 LB 12PK

Product #: 1000009118 Version #: 03 Revision date: 10-25-2018 Issue date: 07-10-2014

SDS US

1 / 11

| Chemical name                               | Common name and synonyms | CAS number | %       |
|---|--------------------------|------------|---------|
| Diethylene Glycol Monoethyl Ether           |                          | 111-90-0   | 1 - 2.5 |
| Disodium Metasilicate                       |                          | 6834-92-0  | 1 - 2.5 |
| Distillates (petroleum), Hydrotreated Light |                          | 64742-47-8 | 1 - 2.5 |
| Isopropyl Alcohol                           |                          | 67-63-0    | 1 - 2.5 |
| Propane                                     |                          | 74-98-6    | 1 - 2.5 |
| d-Limonene                                  |                          | 5989-27-5  | 0.1 - 1 |
| Other components below reportable levels    |                          |            | 80 - 90 |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

|   |   |
|---|---|
| <b>Inhalation</b>   | Move to fresh air. Call a physician if symptoms develop or persist.   |
| <b>Skin contact</b>   | Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse. |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.                       |
| <b>Ingestion</b>  | In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.  |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.                          |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.  |
| <b>General information</b>  | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.   |

#### 5. Fire-fighting measures

|  |  |
|--|--|
| <b>Suitable extinguishing media</b>                                  | Not available.   |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.   |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.  |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.   |
| <b>Fire fighting equipment/instructions</b>                          | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>Specific methods</b>  | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.   |
| <b>General fire hazards</b>  | Extremely flammable aerosol.   |

#### 6. Accidental release measures

|  |  |
|--|--|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.   |
| <b>Methods and materials for containment and cleaning up</b>               | Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.<br><br>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |

**Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage****Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components                      | Type | Value                  |
|---------------------------------|------|------------------------|
| Isopropyl Alcohol (CAS 67-63-0) | PEL  | 980 mg/m3              |
| Propane (CAS 74-98-6)           | PEL  | 400 ppm                |
|                                 |      | 1800 mg/m3<br>1000 ppm |

**US. ACGIH Threshold Limit Values**

| Components                      | Type | Value    |
|---------------------------------|------|----------|
| Butane (CAS 106-97-8)           | STEL | 1000 ppm |
| Isopropyl Alcohol (CAS 67-63-0) | STEL | 400 ppm  |
|                                 | TWA  | 200 ppm  |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                      | Type | Value                  |
|---------------------------------|------|------------------------|
| Butane (CAS 106-97-8)           | TWA  | 1900 mg/m3<br>800 ppm  |
|                                 |      | 1225 mg/m3             |
| Isopropyl Alcohol (CAS 67-63-0) | STEL | 500 ppm                |
|                                 |      | 980 mg/m3              |
|                                 |      | 400 ppm                |
| Propane (CAS 74-98-6)           | TWA  | 1800 mg/m3<br>1000 ppm |

**US. Workplace Environmental Exposure Level (WEEL) Guides**

| Components  | Type | Value     |
|---|------|-----------|
| Diethylene Glycol<br>Monoethyl Ether (CAS 111-90-0) | TWA  | 140 mg/m3 |
|   |      | 25 ppm    |

**Biological limit values****ACGIH Biological Exposure Indices**

| Components                      | Value   | Determinant | Specimen | Sampling Time |
|---------------------------------|---------|-------------|----------|---------------|
| Isopropyl Alcohol (CAS 67-63-0) | 40 mg/l | Acetone     | Urine    | *             |

\* - For sampling details, please see the source document.

|  |  |
|--|--|
| <b>Appropriate engineering controls</b>                                      | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. |
| <b>Individual protection measures, such as personal protective equipment</b> |  |
| <b>Eye/face protection</b>   | Face shield is recommended. Wear safety glasses with side shields (or goggles).  |
| <b>Skin protection</b>   |  |
| <b>Hand protection</b>   | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.  |
| <b>Other</b>   | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.   |
| <b>Respiratory protection</b>  | If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.  |
| <b>Thermal hazards</b>   | Wear appropriate thermal protective clothing, when necessary.  |
| <b>General hygiene considerations</b>  | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.  |

## 9. Physical and chemical properties

### Appearance

|   |  |
|---|--|
| <b>Physical state</b>                               | Gas.                                       |
| <b>Form</b>   | Aerosol.                                   |
| <b>Color</b>  | White.                                     |
| <b>Odor</b>   | Not available.                             |
| <b>Odor threshold</b>                               | Not available.                             |
| <b>pH</b>   | 12.5 - 13.2 estimated                      |
| <b>Melting point/freezing point</b>                 | Not available.                             |
| <b>Initial boiling point and boiling range</b>      | 212 °F (100 °C) estimated                  |
| <b>Flash point</b>                                  | -156.0 °F (-104.4 °C) Propellant estimated |
| <b>Evaporation rate</b>                             | Not available.                             |
| <b>Flammability (solid, gas)</b>                    | Not available.                             |
| <b>Upper/lower flammability or explosive limits</b> |  |
| <b>Flammability limit - lower (%)</b>               | Not available.                             |
| <b>Flammability limit - upper (%)</b>               | Not available.                             |
| <b>Explosive limit - lower (%)</b>                  | Not available.                             |
| <b>Explosive limit - upper (%)</b>                  | Not available.                             |
| <b>Vapor pressure</b>                               | 55 psig @70F estimated                     |
| <b>Vapor density</b>                                | Not available.                             |
| <b>Relative density</b>                             | Not available.                             |
| <b>Solubility(ies)</b>                              |  |
| <b>Solubility (water)</b>                           | Not available.                             |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.                             |
| <b>Auto-ignition temperature</b>                    | Not available.                             |
| <b>Decomposition temperature</b>                    | Not available.                             |
| <b>Viscosity</b>                                    | Not available.                             |
| <b>Other information</b>                            |  |
| <b>Explosive properties</b>                         | Not explosive.                             |
| <b>Oxidizing properties</b>                         | Not oxidizing.                             |

Specific gravity 0.928 estimated

## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | Reacts violently with strong acids. This product may react with oxidizing agents.                                   |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.  |
| <b>Conditions to avoid</b>                | Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not mix with other chemicals. |
| <b>Incompatible materials</b>             | Acids. Strong oxidizing agents. Oxidizing agents. Nitrates. Fluorine. Chlorine.                                     |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.  |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | No adverse effects due to inhalation are expected.           |
| <b>Skin contact</b> | Causes skin irritation. May cause an allergic skin reaction. |
| <b>Eye contact</b>  | Causes eye irritation.                                       |
| <b>Ingestion</b>    | Expected to be a low ingestion hazard.                       |

**Symptoms related to the physical, chemical and toxicological characteristics** Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** May cause an allergic skin reaction.

| <b>Components</b>                                | <b>Species</b> | <b>Test Results</b>                         |
|--|----------------|---|
| Butane (CAS 106-97-8)                            |                |   |
| <b>Acute</b>                                     |                |   |
| <b>Inhalation</b>                                |                |   |
| LC50   | Mouse          | 1237 mg/l, 120 Minutes<br>52 %, 120 Minutes |
|  | Rat            | 1355 mg/l                                   |
| Diethylene Glycol Monoethyl Ether (CAS 111-90-0) |                |   |
| <b>Acute</b>                                     |                |   |
| <b>Dermal</b>                                    |                |   |
| LD50   | Guinea pig     | 5900 mg/kg, Days                            |
|  | Rabbit         | 9143 mg/kg, 24 Hours<br>8500 mg/kg, 2 Hours |
| <b>Oral</b>                                      |                |   |
| LD50   | Guinea pig     | 4970 mg/kg                                  |
|  | Mouse          | 6031 mg/kg                                  |
|  | Rabbit         | 5600 mg/kg                                  |
|  | Rat            | 10502 mg/kg<br>5.4 ml/kg                    |
| Disodium Metasilicate (CAS 6834-92-0)            |                |   |
| <b>Acute</b>                                     |                |   |
| <b>Dermal</b>                                    |                |   |
| LD50   | Rat            | > 5000 mg/kg, 24 Hours                      |
| <b>Inhalation</b>                                |                |   |
| LC50   | Rat            | > 2.06 mg/l, 4 Hours                        |
| <b>Oral</b>                                      |                |   |
| LD50   | Mouse          | 661.5 - 896.3 mg/kg                         |
|  | Rat            | 994.7 - 1335.9 mg/kg                        |

| Components   | Species | Test Results                                |
|--|---------|---|
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) |         |   |
| <b>Acute</b>   |         |   |
| <b>Dermal</b>  |         |   |
| LD50   | Rabbit  | > 2000 mg/kg<br>> 2000 mg/kg, 24 Hours      |
| <b>Inhalation</b>  |         |   |
| LC50   | Rat     | > 7.5 mg/l, 6 Hours<br>> 4.6 mg/l, 4 Hours  |
| <b>Oral</b>  |         |   |
| LD50   | Rat     | > 5000 mg/kg                                |
| d-Limonene (CAS 5989-27-5)                                   |         |   |
| <b>Acute</b>   |         |   |
| <b>Oral</b>  |         |   |
| LD50   | Rat     | > 2000 mg/kg                                |
| Isopropyl Alcohol (CAS 67-63-0)                              |         |   |
| <b>Acute</b>   |         |   |
| <b>Dermal</b>  |         |   |
| LD50   | Rabbit  | 16.4 ml/kg, 24 Hours                        |
| <b>Inhalation</b>  |         |   |
| LC50   | Rat     | > 10000 ppm, 6 Hours                        |
| <b>Oral</b>  |         |   |
| LD50   | Rat     | 5.84 g/kg                                   |
| Propane (CAS 74-98-6)  |         |   |
| <b>Acute</b>   |         |   |
| <b>Inhalation</b>  |         |   |
| LC50   | Mouse   | 1237 mg/l, 120 Minutes<br>52 %, 120 Minutes |
|  | Rat     | 1355 mg/l<br>658 mg/l/4h                    |

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

d-Limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not likely, due to the form of the product.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

| Components   |      | Species   | Test Results                 |
|--|------|---|------------------------------|
| Diethylene Glycol Monoethyl Ether (CAS 111-90-0)             |      |   |                              |
| <b>Aquatic</b>   |      |   |                              |
| Fish   | LC50 | Bluegill (Lepomis macrochirus)                      | > 10000 mg/l, 96 hours       |
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) |      |   |                              |
| <b>Aquatic</b>   |      |   |                              |
| Fish   | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 2.9 mg/l, 96 hours           |
| d-Limonene (CAS 5989-27-5)                                   |      |   |                              |
| <b>Aquatic</b>   |      |   |                              |
| Crustacea  | EC50 | Water flea (Daphnia pulex)                          | 69.6 mg/l, 48 hours          |
| Fish   | LC50 | Fathead minnow (Pimephales promelas)                | 0.619 - 0.796 mg/l, 96 hours |
| Isopropyl Alcohol (CAS 67-63-0)                              |      |   |                              |
| <b>Aquatic</b>   |      |   |                              |
| Algae  | IC50 | Algae   | 1000.0001 mg/L, 72 Hours     |
| Crustacea  | EC50 | Daphnia   | 13299 mg/L, 48 Hours         |
| Fish   | LC50 | Bluegill (Lepomis macrochirus)                      | > 1400 mg/l, 96 hours        |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

### Bioaccumulative potential

#### Partition coefficient n-octanol / water (log Kow)

|                                   |       |
|-----------------------------------|-------|
| Butane                            | 2.89  |
| Diethylene Glycol Monoethyl Ether | -0.54 |
| d-Limonene                        | 4.232 |
| Isopropyl Alcohol                 | 0.05  |
| Propane                           | 2.36  |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## 14. Transport information

### DOT

|                                   |  |
|-----------------------------------|--|
| <b>UN number</b>                  | UN1950   |
| <b>UN proper shipping name</b>    | Aerosols, flammable, (each not exceeding 1 L capacity) |
| <b>Transport hazard class(es)</b> |  |
| <b>Class</b>                      | 2.1  |

|                                     |   |
|-------------------------------------|---|
| <b>Subsidiary risk</b>              | -   |
| <b>Label(s)</b>                     | 2.1   |
| <b>Packing group</b>                | Not applicable.   |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | N82   |
| <b>Packaging exceptions</b>         | 306   |
| <b>Packaging non bulk</b>           | None  |
| <b>Packaging bulk</b>               | None  |

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

**IATA**

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1950  |
| <b>UN proper shipping name</b>      | Aerosols, flammable   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 2.1   |
| <b>Subsidiary risk</b>              | -   |
| <b>Label(s)</b>                     | 2.1   |
| <b>Packing group</b>                | Not applicable.   |
| <b>Environmental hazards</b>        | Yes   |
| <b>ERG Code</b>                     | 10L   |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| <b>Other information</b>            |   |
| <b>Passenger and cargo aircraft</b> | Allowed with restrictions.  |
| <b>Cargo aircraft only</b>          | Allowed with restrictions.  |
| <b>Packaging Exceptions</b>         | LTD QTY   |

**IMDG**

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1950  |
| <b>UN proper shipping name</b>      | AEROSOLS  |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 2.1   |
| <b>Subsidiary risk</b>              | -   |
| <b>Label(s)</b>                     | None  |
| <b>Packing group</b>                | Not applicable.   |
| <b>Environmental hazards</b>        |   |
| <b>Marine pollutant</b>             | Yes   |
| <b>EmS</b>                          | F-D, S-U  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| <b>Packaging Exceptions</b>         | LTD QTY   |

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT**





IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

No

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

#### Safe Drinking Water Act (SDWA)

Not regulated.

### US state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Butane (CAS 106-97-8)  
Isopropyl Alcohol (CAS 67-63-0)

**US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8)  
Isopropyl Alcohol (CAS 67-63-0)  
Propane (CAS 74-98-6)

**US. New Jersey Worker and Community Right-to-Know Act**

Butane (CAS 106-97-8)  
Isopropyl Alcohol (CAS 67-63-0)  
Propane (CAS 74-98-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Butane (CAS 106-97-8)  
Isopropyl Alcohol (CAS 67-63-0)  
Propane (CAS 74-98-6)

**US. Rhode Island RTK**

Butane (CAS 106-97-8)  
Isopropyl Alcohol (CAS 67-63-0)  
Propane (CAS 74-98-6)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Benzene (CAS 71-43-2) Listed: February 27, 1987

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

2-Ethoxyethanol (CAS 110-80-5) Listed: January 1, 1989  
Benzene (CAS 71-43-2) Listed: December 26, 1997  
Ethylene Glycol (CAS 107-21-1) Listed: June 19, 2015  
Ethylene Glycol Monomethyl Ether (CAS 109-86-4) Listed: January 1, 1989

**US - California Proposition 65 - CRT: Listed date/Male reproductive toxin**

2-Ethoxyethanol (CAS 110-80-5) Listed: January 1, 1989  
Benzene (CAS 71-43-2) Listed: December 26, 1997  
Ethylene Glycol Monomethyl Ether (CAS 109-86-4) Listed: January 1, 1989

**International Inventories**

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia                   | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand                 | New Zealand Inventory  | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 07-10-2014  
**Revision date** 10-25-2018  
**Version #** 03

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.