

TERAND

The Maintenance Professional's Choice

RTV SILICONE CAULK & SEALANT

117 - Clear

This R.T.V. Silicone Caulk and Sealant is ideal for use wherever a strong permanently elastic weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Ideal for caulking windows, doors, sills and ceiling cracks and crevices. Features excellent adhesion and high chemical resistance. Will not sag or shrink during severe temperature changes. Useful for sealing cracks in machinery, heating and ventilation duct work, plumbing fixtures, electrical connections and low pressure water and drain lines.



FEATURES

- Seals, Bonds, Insulates • Flexible • Easy to Use
- Waterproof • Weatherproof
- 100% RTV Silicone - Industrial Strength
- Flexible from -60°F to +500°F
- Caulks tubs, sinks, showers and plumbing fixtures
- Seals windows, doors, tile, marble, etc.
- Bonds almost any material

FOR USE ON

Bonds nameplates, machinery flanges, glass, signs, electrical insulation, etc. Offers unmatched performance under the most severe conditions. Remains flexible and will not shrink, crack, crumble or dry out.

NOTE: Paint will not adhere to cured material. Not recommended for continuous immersion in water or application to porous surfaces such as masonry.

Characteristics:

Temperature Range	Cures at room temperature, range from -76°F to 350°F
Waterproof	Yes
Appearance	Clear Paste
Shipping Weight	12 pounds

Seals, Bonds, Insulates
Flexible • Easy to Use
Waterproof • Weatherproof
100% RTV Silicone - Industrial Strength
Flexible from -60°F to +500°F
Caulks tubs, sinks, showers and plumbing fixtures
Seals windows, doors, tile, marble
Bonds almost any material

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER. SEE OTHER CAUTIONS ON BACK PANEL. KEEP OUT OF REACH OF CHILDREN.
NET WT. 8 OZ. (227 Grams)

www.cpaeroscience.com
(800) 327-1835

